

UHF Dual-Channel, Long Range
True Diversity Professional Wireless Microphone System

DWS-612

DWS-612

Dual-Channel, True Diversity Professioal Wireless Microphone System

















DWS-612 is a UHF Professional wireless microphone system with sophisticated and most advanced functions. The built-in channel-scanning works with the industry-leading channel synchronizing technology to rapidly complete setting of non-interference channels. High contrast LCD display on the front panel, with optional detachable UHF coaxial antenna make this system flexible in the most challenging spaces to improve signal performance, ensures stable and reliable signal reception and can be paired with passive splitters and powered distribution system, including battery status, RF signal status, and input volume of the connected transmitter to ensure the best sound quality. Easily complies various audio applications.

FEATURES

- Adjustable SQ Increases receiver range with higher sensitivity and reduces interference with lower sensitivity.
- Pilotone, noise-detector and squelch circuits prevent noise, interference and improve operation distance.
- Auto Scanning feature rapidly discover for an interference-free working frequency and channel.
- Suitable volume gain control(s) and switch selection in-between MIC-LINE output level.
- Mixed audio output jack: balanced XLR or unbalanced 6.3mm
- RF Level, Channel, frequency, AF level antenna selection.
- Audio output jacks: balanced XLR or unbalanced 6.3mm.
- Connected transmitter battery status.





True diversity reception

With the most advanced true diversity reception, it provides quality performance with high-stability reception and no dropouts even over long distances. with lower sensitivity.

No more noise

Industry standard pilotone, noise-detector and squelch circuits prevent noise interference. Adjustable SQ to increase receiver range with higher sensitivity and reduce interference with lower sensitivity.





Real-time display

High contrast LCD on the front panel displays antenna selection status and setting details, as well as monitoring the battery status and input volume of the connected transmitter for the audio engineer to handle and ensure the best sound quality.

Antenna Distribution

UHF detachable antennas are designed to enhance wireless audio transmission range, covering the 500-960 MHz frequency band. It ensures stable and reliable signal reception and can be paired with adapters and the UHF antenna booster and antenna dividers for improved signal performance in various audio applications.



DWS-612

DWS-612		
EIA standard 19" metal 1/2U		
True Diversity		
UHF 500 - 960 MHz		
25 MHz		
Dual		
100		
RX <->TX		
50 Hz - 18 KHz		
± 40 KHz		
S/N > 80 dBm at 10 dBµV		
> 110 dB(A)		
< 0.5% @ 1 KHz		
Detachable at rear-end, TNC female.		
PLL synthesized, frequency stability ± 0.00	5% (-10 - +60°C)	
Pilotone & Noise-cancelling dual-squelch	circuit	
Balanced XLR and unbalanced Ø6.3mm		
Gain control circuit for adjustment of out	out volume	
MIC-LINE		
12V DC /1.0A		
200 x 150 x 44		
	True Diversity UHF 500 - 960 MHz 25 MHz Dual 100 RX <->TX 50 Hz - 18 KHz ± 40 KHz \$/N > 80 dBm at 10 dBµV > 110 dB(A) < 0.5% @ 1 KHz Detachable at rear-end, TNC female. PLL synthesized, frequency stability ± 0.00 Pilotone & Noise-cancelling dual-squelch Balanced XLR and unbalanced Ø6.3mm Gain control circuit for adjustment of outs MIC-LINE 12 V DC /1.0A	



Compatible



DWS-81
Rechargeable Handheld
Microphone



DWS-82
Rechargeable Bodypack
Microphone



DWS-83
Wireless Gooseneck
Microphone

Accessories



DWS-HC92

Daul-Slot
Charging Station



DWS-MC16+ Uni-Directional Lavalier Microphone



DWS-MC201

Dual-Sided Uni-Directional

Waterproof Headworn

Microphone



DWS-MC77
Uni-Directional
Headset Microphone



DWS-MC61B Single-Sided Uni-Directional Earworn Microphone



DWS-DA80
Wideband
Directional Antenna



DWS-AD85
Wideband 4-Channel
Antenna Divider



DWS-AB80 UHF Antenna Booster



DWS-AD50F
Passive Antenna
Divider Pack



DWS-FM801 Rear-to-Front Cabels



